

DA 3496

Slimline cooker hood
with energy-efficient LED lighting and light-touch switches for easy use.



- Elegant design - slim 895mm extractor canopy
- Powerful - 550m³/h on the booster setting
- Efficient filtration- 10-ply stainless-steel grease filter
- Safe and easy to clean - Miele CleanCover
- Suitable for every home - for extraction or recirculation

EAN: 4002515562239 / material number: 10081920

Construction type	
Slimline cooker hood •	
Design	
Colour Stainless steel	
Operating modes	
Type of air guide Convertible	
Recirculation conversion kit (order separately) DUU 151	
User convenience	
Electronic controls •	
Light-touch controls •	
Power levels (excluding booster levels) 3	
Programmable Booster level switch-off •	
Cleaning convenience	
Easy-to-clean canopy interior – CleanCover •	
Filter system	
Number of dishwasher safe stainless steel grease filters 2	
Lighting	
LED •	
Light intensity in Lx 300	
Colour temperature in K 3,000	
Fan	
Dual-action fan •	
AC motor •	
Air throughput with max. duct diameter in extraction mode (not for external version)	
Air throughput in Level 1 (m ³ /h) 150	
Air throughput in Level 2 (m ³ /h) 275	
Air throughput in Level 3 (m ³ /h) 400	
Air throughput in booster level 1 (m ³ /h) 550	
Sound power in Level 1 (dB(A) re 1 pW) 45	
Sound power in Level 2 (dB(A) re 1 pW) 51	
Sound power in Level 3 (dB(A) re 1 pW) 56	
Sound power in booster level 1 (dB(A) re1pW) 64	
Sound pressure in Level 1 (dB(A) re 20 µPa) 32	
Sound pressure in Level 2 (dB(A) re 20 µPa) 39	
Sound pressure in Level 3 (dB(A) re 20 µPa) 44	
Sound pressure in booster level 1 (dB(A) re20µPa)	52
	52
Sound pressure in booster level 2 (dB(A) re20µPa)	52
	52

more information:
<http://www.miele.co.uk/domestic>

For further information please see next page...

